

Model No.	CHIPSET (IMAGE SENSOR)	FEATURE	\$
DS-2CE16C0T-IRP	1.0MP HD720P 1/3" CMOS	1.0Megapixel high-performance CMOS, Analog HD output, up to 720P resolution, True Day/Night, DNR, Smart IR, Up to 20m IR distance, IP66 weatherproof.	Call
DS-2CE16D0T-IRP	2MP HD1080P 1/3" CMOS	2.0Megapixel high-performance CMOS, Analog HD output, up to 1080P resolution, True Day/Night, DNR, Smart IR, Up to 20m IR distance, IP66 weatherproof.	Call
DS-2CE16C2T-IR	1.3MP HD720P 1/3" CMOS	1.3Megapixel high-performance CMOS, Analog HD output, up to 720P resolution, True Day/Night, DNR, Smart IR, Up to 20m IR distance, IP66 weatherproof.	Call
DS-2CE16C2T-IT3	1.3MP HD720P 1/3" CMOS	1.3Megapixel high-performance CMOS, Analog HD output, up to 720P resolution, True Day/Night, DNR, Smart IR, Up to 40m IR distance, IP66 weatherproof.	Call
DS-2CE16D1T-IT3	2MP HD1080P 1/3" CMOS	2 Megapixel high-performance CMOS, Analog HD output, up to 1080P resolution, True Day/Night, Smart IR, EXIR technology, 40m IR distance, IP66 weatherproof, Up the Coax(HIKVISION-C Protocol OSD menu.	Call
DS-2CE16D1T-(A)V FIR3	2MP HD1080P 1/3" CMOS	2 Megapixel high-performance CMOS, Analog HD output, up to 1080P resolution, 2.8 – 12mm vari-focal lens, True Day/Night, Smart IR, Up to 40m IR distance, IP66 weatherproof, OSD menu, 24V AC/ 12V DC (-A), Up the Coax(HIKVISION-C Protocol)	Call
DS-2CE16D5T-(A)V FIT3	2MP HD1080P 1/3" CMOS	2 Megapixel high-performance CMOS, Analog HD output, up to 1080P resolution, 2.8-12mm vari-focal lens, True Day/Night, OSD menu, 3D DNR, Smart IR, True WDR, up to 120dB, Up to 50m IR distance, IP66 weatherproof, Up the Coax(HIKVISION-C, Pelco-C Protocol), 24V AC/ 12V DC (-A)	Call
DS-2CC12D9T(-A)	2MP HD1080P 1/3" CMOS	2 Megapixel high-performance CMOS, Analog HD output, up to 1080P resolution, True Day/Night, OSD menu, 3D DNR, Smart IR, True WDR, up to 120dB, Up the Coax(HIKVISION-C), A: AC24V/DC12V	Call
DS-2CE56C0T-IRP	1MP HD720P 1/3" CMOS	1 Megapixel high-performance CMOS, Analog HD output, up to 1080P resolution, True Day/Night, Smart IR, EXIR technology, up to 20m IR distance, IP66 weatherproof, OSD menu, Up the Coax(HIKVISION-C Protocol)	Call
DS-2CE56D0T-IRP	2MP HD1080P 1/3" CMOS	2Megapixel high-performance CMO, Analog HD output, up to 720P resolution, True Day/Night, DNR, Smart IR, EXIR technology ,up to 20m IR distance, IP66 weatherproof, Up the Coax(HIKVISION-C Protocol)	Call
DS-2CE56C2T-IT3	1.3MP HD720P 1/3" CMOS	1.3 Megapixel high-performance CMOS, Analog HD output, up to 720P resolution, True Day/Night, DNR, Smart IR, EXIR technology, up to 20m/40m IR distance, IP66 weatherproof.	Call
DS-2CE56D1T-IT3	2MP HD1080P 1/3" CMOS	2 Megapixel high-performance CMOS, Analog HD output, up to 1080P resolution, True Day/Night, Smart IR, EXIR technology, up to 20/40m IR distance, IP66 weatherproof, Up the Coax(HIKVISION-C Protocol)	Call
DS-2CE56D1T-VP IR	2MP HD1080P 1/3" CMOS	2 Megapixel high-performance CMOS, Analog HD output, up to 1080P resolution, True Day/Night, Smart IR, Up to 20m IR distance, IP66 weatherproof & vandal-proof, OSD menu, Up the Coax(HIKVISION-C Protocol)	Call

DS-2CE56D5T-VFIR	2MP HD1080P 1/3" CMOS	Turbo HD1080P Vari-focal Dome, Len 2.8-12mm Dome Camera HD1080p, 1/3" CMOS, 24 pcs IR LEDs, 30m IR, Indoor IR Vari-focal Dome, Len 2.8-12mm ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, 3D DNR, OSD Menu (Up the Coax), Digital WDR, 2.8~12mm Lens, Full HD1080P video output, Long transmission distance Up to 500 & 700m over normal coaxial cable.	Call
DS-2CE56D1T-VPIR3Z	2MP HD1080P 1/3" CMOS	2 Megapixel high-performance CMOS, Analog HD output, up to 1080P resolution, 2.8-12mm motorized vari-focal lens, True Day/Night, OSD menu, 3D DNR, Smart IR, True WDR, up to 120dB, Up to 30m IR distance, Up the Coax (HIKVISION-C, Pelco-C Protocol), 24V AC/ 12V DC (-A)	Call
DS-2CE56D5T-AVFIR	2MP HD1080P 1/3" CMOS	2 Megapixel high-performance CMOS, Analog HD output, up to 1080P resolution, 2.8 – 12mm vari-focal lens, True Day/Night, Smart IR, Up to 40m IR distance, IP66 weatherproof, OSD menu, 24V AC/ 12V DC (-A), Up the Coax (HIKVISION-C Protocol)	Call
DS-2AE5123TI-A	1.3MP HD720P 1/3" CMOS	1.3MP CMOS Image Sensor, 1280x720/1920x1080, 23X optical zoom, 16X digital zoom, DWDR, Up to 150m IR distance, 3D intelligent positioning, Support Turbo HD and BNC output	Call