

Series	Model	Picture	Parameter
HD-CVI DVR 720P			
smart 1U 1HDD 720P	HCVR4104HS-S2		>Support HDCVI/Analog/IP Video input >H.264 dual-stream video compression >HCVR4104/4108: All channel 720P recording >4/8/ channel synchronous playback, GRID interface & smart search >8/8/16ch alarm input, 3ch relay output >HDMI/VGA simultaneous video output >Support 1 SATA HDDs up to 4TB, 2 USB2.0 >ONVIF Version 2.4 conformance >3D intelligent positioning with Dahua PTZ dome camera >Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS)
	HCVR4108HS-S2		
	HCVR4116HS-S2		
smart 1U 1HDD 720P	HCVR4208A-S2		>Support HDCVI/Analog/IP Video input >H.264 dual-stream video compression >HCVR4204/4208/4216A-S2: All channel 720P recording >4/8/16 channel synchronous playback, GRID interface & smart search >8/8/16ch alarm input, 3ch relay output >HDMI/VGA simultaneous video output >Support 2 SATA HDDs up to 8TB, 2 USB2.0 >ONVIF Version 2.4 conformance >3D intelligent positioning with Dahua PTZ dome camera >Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS)
	HCVR4216AN-S2		
mini 1U 1HDD 720P	iHCVR5104H-F		4/8ch Mini 1U face detection IHCVR
	iHCVR5108H-F		
smart 1U 1HDD 720P	HCVR5104C-V2		with 1080p realtime preview H.264 dual-stream video compression All channel 720P HDMI / VGA simultaneous video output all channel synchronous realtime playback, GRID interface & smart search 3D intelligent positioning with Dahua PTZ dome camera Support 1 SATA HDD up to 4TB, 2 USB2.0 Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
	HCVR5108C-V2		
mini 1U 1HDD 720P	HCVR5104H-S2		720P realtime, Mini 1U Case,1 HDMI/1 VGA,4/8ch Video in,1 RJ45(100M), 1 Audio in/1 Audio out,1 RS485,2 USB, 1 HDD
	HCVR5108H-S2		
2U 8HDD 720P	HCVR5816S-S2		720P realtime, 2U Case,1 HDMI/1 VGA/1 TV,4/8/16ch Video in,1 RJ45(100M), 4/8/16 Audio in/1 Audio out,4/8/16 Alarm in/6 Alarm out, 1 RS485,4 USB, 8 HDD
1.5U4HDD 720P	HCVR5424L		>Up to 24/32 cameras with 1080p realtime preview >H.264 dual-stream video compression >HCVR5424/5432L: All channel 720P >2HDMI/VGA/TV simultaneous video output >16 channel synchronous realtime playback, GRID interface & smart search >3D intelligent positioning with Dahua PTZ dome camera >Support 4 SATA HDDs up to 16TB, 1 eSATA up to 16TB,3 USB2.0 >Multiple network monitoring: Web viewer, CMS(DSS/PSS)&DMSS
1.5U 4HDD 720P	HCVR5432L		
2U 8HDD 720P	HCVR5824S		>Up to 24/32 cameras with 1080p realtime preview >H.264 dual-stream video compression >HCVR5824/5832S: All channel 720P >2HDMI/VGA/TV simultaneous video output >16 channel synchronous realtime playback, GRID interface & smart search >3D intelligent positioning with Dahua PTZ dome camera >Support 8 SATA HDDs up to 32TB, 1 eSATA up to 16TB,4 USB2.0 >Multiple network monitoring: Web viewer, CMS(DSS/PSS)&DMSS
2U 8HDD 720P	HCVR5832S		
HD-CVI DVR 1080P			
mini 1U 1HDD 1080P	HCVR7104H-S2		4/8ch mini 1U HD CVI DVR
	HCVR7108H-S2		
1U 2HDD 1080P	HCVR7204A-S2		4/8ch 1U HD CVI DVR
	HCVR7208A-S2		

	HCVR7416L		>Tribrid: Each channel supports HDCVI/Analog/IP Video input >1HDMI/VGA/TV simultaneous video output,1 HDMI separate output >HCVR7404/7408/7416L:All channel Max 1080P >Up to 1080p realtime live view >H.264 dual-stream video compression >4/8 channel synchronous realtime playback, GRID interface & smart search >Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotech , and etc. >3D intelligent positioning with Dahua PTZ dome camera >Support 4 SATA HDDs up to 16TB, 1 eSATA up to 16TB,3 USB2.0 >Multiple network monitoring: Web viewer, CMS(DSS/PSS)&DMSS
	HCVR7804S		>Tribrid: Each channel supports HDCVI/Analog/IP Video input >1HDMI/VGA/TV simultaneous video output,1 HDMI separate output >HCVR7804/7808/7816S:All channel Max 1080P >Up to 1080p realtime live view >H.264 dual-stream video compression >4/8 channel synchronous realtime playback, GRID interface & smart search >Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotech , and etc. >ONVIF Version 2.2 conformance >3D intelligent positioning with Dahua PTZ camera >Support 8 SATA HDDs up to 32TB, 1 eSATA up to 16TB,4USB2.0 >Multiple network monitoring: Web viewer, CMS(DSS/PSS)&DMSS
	HCVR7808S		
	HCVR7816S		
HDCVI CAMERA 720P (1Megapixel)			
	HAC-HFW1100RP		1Megapixel 720P Water-proof HDCVI IR-Bullet Camera
	HAC-HDW1100RP		1Megapixel 720P HDCVI IR-dome Camera
	HAC-HFW1100S		1Megapixel 720P Waterproof IR HDCVI Camera 25/30fps@720P, ICR, IP66 Max. IR Led length: 20m, Smart IR 6mm fixed length(2.8mm, 3.6mm, 8mm optional) Default: Bracket included
	HAC-HDW1100S		1Megapixel 720P Waterproof IR HDCVI Camera 25/30fps@720P, ICR Max. IR Led length: 20m, Smart IR 3.6mm fixed length(2.8mm, 6mm, 8mm optional)
	HAC-HDW1100C		1Megapixel 720P Waterproof IR HDCVI Camera 25/30fps@720P, ICR Max. IR Led length: 20m, Smart IR 3.6mm fixed length(2.8mm, 6mm, 8mm optional)
	HAC-HDW1100M		1Megapixel 720P Waterproof IR HDCVI Camera 25/30fps@720P, ICR, IP66 Max. IR Led length: 20m, Smart IR 3.6mm fixed lens(2.8mm, 6mm, 8mm optional)
	HAC-HFW1100B		1Megapixel 720P Waterproof IR HDCVI Camera 25/30fps@720P, ICR, IP66 Max. IR Led length: 30m, Smart IR 6mm fixed lens(2.8mm, 3.6mm, 8mm optional)
	HAC-HFW1100D		1Megapixel 720P Waterproof IR HDCVI Camera 25/30fps@720P, ICR, IP66 Max. IR Led length: 50m, Smart IR 8mm fixed lens(3.6mm, 6mm,12mm, 16mm optional)
ZOOM LENS	HAC-HFW1100R-VF		>1Megapixel 1/2.9" CMOS >25/30fps@720P >High speed, long distance real-time transmission >Day/Night(ICR), AWB, AGC, BLC, 2D-DNR >2.7~12mm vari-focal lens >Max. IR LEDs length 30m, Smart IR >IP66, DC12V
	HAC-HDBW1100R-VF		>1Megapixel 1/2.9" CMOS >25/30fps@720P >High speed, long distance real-time transmission >Day/Night(ICR), AWB, AGC, BLC, 2D-DNR >2.7~12mm vari-focal lens >Max. IR LEDs length 30m, Smart IR >IP66, IK10, DC12V
HDCVI CAMERA 720P (1.3Megapixel)			

	HAC-HFW3101		1.3Megapixel 720P WDR HD CVI camera
	HAC-HFW2120B		1.3Megapixel 720P Waterproof IR HDCVI Camera 50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 30m, Smart IR HD and standard definition switch 6mm fixed length(2.8mm, 3.6mm, 8mm optional)
	HAC-HFW2120B-B		1.3Megapixel 720P Waterproof IR HDCVI Camera 50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 30m, Smart IR HD and standard definition switch 6mm fixed lens(2.8mm, 3.6mm, 8mm optional) Default: Bracket included
	HAC-HFW2120D		1.3Megapixel 720P Waterproof IR HDCVI Camera 50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 50m, Smart IR HD and standard definition switch 8mm fixed lens(3.6mm, 6mm, 12mm, 16mm optional)
	HAC-HFW2120D-B		1.3Megapixel 720P Waterproof IR HDCVI Camera 50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 50m, Smart IR HD and standard definition switch 8mm fixed lens(3.6mm, 6mm, 12mm, 16mm optional) Default: Bracket included
	HAC-HDW2120S		1.3Megapixel 720P Waterproof IR HDCVI Camera 50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 20m, Smart IR HD and standard definition switch 3.6mm fixed length(2.8mm, 6mm, 8mm optional)
	HAC-HFW2120S		1.4Megapixel 720P Waterproof IR HDCVI Camera 50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 20m, Smart IR HD and standard definition switch 6mm fixed length(2.8mm, 3.6mm, 8mm optional) Default: Bracket included
	HAC-HDW2120M		1.4Megapixel 720P Waterproof IR HDCVI Camera 50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 20m, Smart IR HD and standard definition switch 6mm fixed length(2.8mm, 3.6mm, 8mm optional) Default: Bracket included
	HAC-HDBW2120E		1.4Megapixel 720P Waterproof IR HDCVI Camera 50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 20m, Smart IR HD and standard definition switch 6mm fixed length(2.8mm, 3.6mm, optional) Default: Bracket included
	HAC-HFW2120R-VF		> 1.4Megapixel 1/2.9" CMOS >25/30fps@720P >High speed, long distance real-time transmission >Day/Night(ICR), AWB, AGC, BLC, 2D-DNR >2.7~12mm vari-focal lens >Max. IR LEDs length 30m, Smart IR >IP66, DC12V
	HAC-HDBW2120R-VF		> 1.4Megapixel 1/2.9" CMOS >25/30fps@720P >High speed, long distance real-time transmission >Day/Night(ICR), AWB, AGC, BLC, 2D-DNR >2.7~12mm vari-focal lens >Max. IR LEDs length 30m, Smart IR >IP66, IK10, DC12V
	HAC-HFW2120R-Z		> 1.4Megapixel 1/2.9" CMOS >25/30fps@720P >High speed, long distance real-time transmission >Day/Night(ICR), AWB, AGC, BLC, 2D-DNR >2.7~12mm vari-focal lens >Max. IR LEDs length 30m, Smart IR >IP66, IK10, DC12V
	HAC-HDBW2120R-Z		> 1.4Megapixel 1/2.9" CMOS >25/30fps@720P >High speed, long distance real-time transmission >Day/Night(ICR), AWB, AGC, BLC, 2D-DNR >2.7~12mm vari-focal lens >Max. IR LEDs length 30m, Smart IR >IP66, IK10, DC12V
	HAC-HFW2100E		1.4Megapixel 720P Waterproof IR HDCVI Camera 50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 20m, Smart IR HD and standard definition switch 6mm fixed length(2.8mm, 3.6mm, 8mm optional) Default: Bracket included
HDCVI CAMERA 1080P (2Megapixel)			

	HAC-HFW1200R		>2Megapixel 1/2.7" CMOS >25/30fps@1080P >High speed, long distance real-time transmission >Day/Night(ICR), AWB, AGC, BLC, 2D-DNR >3.6mm fixed lens (6mm optional) >Max. IR LEDs length 20m, Smart IR >IP66, DC12V
	HAC-HFW1200RM		>2Megapixel 1/2.7" CMOS >25/30fps@1080P >High speed, long distance real-time transmission >Day/Night(ICR), AWB, AGC, BLC, 2D-DNR >3.6mm fixed lens (6mm optional) >Max. IR LEDs length 20m, Smart IR >IP66, DC12V , material:metal
	HAC-HDW1200M		> 2Megapixel 1/2.7" CMOS >25/30fps@1080P >High speed, long distance real-time transmission >Day/Night(ICR), AWB, AGC, BLC, 2D-DNR >3.6mm fixed lens (6mm optional) >Max. IR LEDs length 20m, Smart IR >IP66, DC12V , material:metal
	HAC-HDW2220M		2.4Megapixel 1080P Waterproof IR HDCVI Camera 25/30fps@1080P, 25/30/50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 20m, Smart IR HD and standard definition switch 6mm fixed length(2.8mm, 3.6mm, 8mm optional) Default: Bracket included
	HAC-HDW2220S		2.4Megapixel 1080P Waterproof IR HDCVI Camera 25/30fps@1080P, 25/30/50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 20m, Smart IR HD and standard definition switch 3.6mm fixed length(2.8mm, 6mm, 8mm optional)
	HAC-HFW2220E		2.4Megapixel 1080P Water-proof HDCVI IR-Bullet Camera
	HAC-HFW2220B		2.4Megapixel 1080P Waterproof IR HDCVI Camera 25/30fps@1080P, 25/30/50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 30m, Smart IR HD and standard definition switch 6mm fixed length(2.8mm, 3.6mm, 8mm optional)
	HAC-HFW2220B-B		2.4Megapixel 1080P Waterproof IR HDCVI Camera 25/30fps@1080P, 25/30/50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 30m, Smart IR HD and standard definition switch 6mm fixed lens(2.8mm, 3.6mm, 8mm optional) Default: Bracket included
	HAC-HFW2220D		2.4Megapixel 1080P Waterproof IR HDCVI Camera 25/30fps@1080P, 25/30/50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 50m, Smart IR HD and standard definition switch 8mm fixed lens(3.6mm, 6mm,12mm, 16mm optional)
	HAC-HFW2220D-B		2.4Megapixel 1080P Waterproof IR HDCVI Camera 25/30fps@1080P, 25/30/50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 50m, Smart IR HD and standard definition switch 8mm fixed lens(3.6mm, 6mm,12mm, 16mm optional) Default: Bracket included
	HAC-HFW2220S		2.4Megapixel 1080P Waterproof IR HDCVI Camera 25/30fps@1080P, 25/30/50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 20m, Smart IR HD and standard definition switch 6mm fixed length(2.8mm, 3.6mm, 8mm optional) Default: Bracket included
	HAC-HDBW2220E		2.4Megapixel 1080P Waterproof IR HDCVI Camera 25/30fps@1080P, 25/30/50/60fps@720P, ICR, OSD, IP66 Max. IR Led length: 20m, Smart IR HD and standard definition switch 6mm fixed length(2.8mm, 3.6mm, 8mm optional) Default: Bracket included
	HAC-HFW2220R-VF		>2.4Megapixel 1/2.9" CMOS >25/30fps@720P >High speed, long distance real-time transmission >Day/Night(ICR), AWB, AGC, BLC, 2D-DNR >2.7-12mm vari-focal lens >Max. IR LEDs length 30m, Smart IR >IP66, DC12V
	HAC-HDBW2220R-VF		>2.4Megapixel 1/2.9" CMOS >25/30fps@720P >High speed, long distance real-time transmission >Day/Night(ICR), AWB, AGC, BLC, 2D-DNR >2.7-12mm vari-focal lens >Max. IR LEDs length 30m, Smart IR >IP66, DC12V

	HAC-HFW2220R-Z		>2.4Megapixel 1/2.9" CMOS >25/30fps@720P >High speed, long distance real-time transmission >Day/Night(ICR), AWB, AGC, BLC, 2D-DNR >2.7~12mm vari-focal lens >Max. IR LEDs length 30m, Smart IR >IP66, DC12V
	HAC-HDBW2220R-Z		>2.4Megapixel 1/2.9" CMOS >25/30fps@720P >High speed, long distance real-time transmission >Day/Night(ICR), AWB, AGC, BLC, 2D-DNR >2.7~12mm vari-focal lens >Max. IR LEDs length 30m, Smart IR >IP66, DC12V
HD HDCVI PTZ DOME CAMERA 720P(1Megapixel)			
	SD40C112I-HC		>Powerful 12x optical zoom >25/30/50/60fps@720P >DWDR, Day/Night (ICR), DNR (2D&3D), Auto iris, Auto focus, AWB, AGC, BLC >Max 300°/s pan speed, 360° continuous pan rotation >Control over coaxial cable, long distance real-time transmission >Up to 255 presets, 5 auto scan, 8 tour, 5 pattern >Built-in 2/1 alarm in/out >Support intelligent 3D positioning with DH-SD protocol >IP66, OSD
	SD42C112I-HC		
	SD63120I-HC		- Max 300 °/s pan speed 1ch audio in 2/1ch alarm in/out - IP 66, IK 10 optional -40~60°C
	SD59112I-HC		>Powerful 12x optical zoom >25/30/50/60fps@720P >DWDR, Day/Night (ICR), DNR (2D&3D), Auto iris, Auto focus, AWB, AGC, BLC >Max 400°/s pan speed, 360° continuous pan rotation >Control over coaxial cable, long distance real-time transmission >Up to 300 presets, 5 auto scan, 8 tour, 5 pattern >Built-in 2/1 alarm in/out >Support intelligent 3D positioning with DH-SD protocol >IP66
	SD6C120I-HC		- Max 240 °/s pan speed 1ch audio in 2/1ch alarm in/out - IP66, -40~60°C - IR Distance: 100m
	SD63220I-HC		- Max 300 °/s pan speed 1ch audio in 2/1ch alarm in/out - IP 66, IK 10 optional -40~60°C
	SD6C220I-HC		- Max 240 °/s pan speed 1ch audio in 2/1ch alarm in/out - IP66, -40~60°C - IR Distance: 100m
	SD59220I-HC		>12x optical zoom >Max. 25/30fps@1080P(1920X1080) & 20/30/50/60fps@720P resolution >DWDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus >Max 400°/s pan speed, 360° endless pan rotation >Up to 300 presets, 5 auto scan, 8 tour, 5 pattern >Built-in 2/1 alarm in/out >Support intelligent 3D positioning with DH-SD protocol >IR Distance up to 100m >IP66
	SD40C212I-HC		>Powerful 12x optical zoom >Max. 25/30fps@1080P >DWDR, Day/Night (ICR), DNR (2D&3D), Auto iris, Auto focus, AWB, AGC, BLC >Max 300°/s pan speed, 360° continuous pan rotation >Control over coaxial cable, long distance real-time transmission >Up to 255 presets, 5 auto scan, 8 tour, 5 pattern >Built-in 2/1 alarm in/out >Support intelligent 3D positioning with DH-SD protocol >IP66, OSD
	SD42C212I-HC		