

Model	Picture	Product Description	Model	Picture	Product Description
TRC 010 4CH		4 Channel DVR Solution: H.264, Dual-Stream, Multi-channel synchro playback, HDMI, VGA, CVBS output, 2*USB 2.0, RS485, Include CVMS (Central Video Management Software) and Mobile Surveillance Application, IR remote control and mouse operation, 4-ch video&1-ch audio input, 1 SATA interface, WD1/4CIF/2CIF: 12 fps/ch, 1U case.CIF real-time recording, 1 SATA interface, HDMI output, Video loop out optional, Front panel buttons optional, Alarm I/O: 4/1 and 4 audio input optional.	TRC 011 8CH		8 Channel DVR Solution: H.264, Dual-Stream, Multi-channel synchro playback, HDMI, VGA, CVBS output, 2*USB 2.0, RS485, Include CVMS (Central Video Management Software) and Mobile Surveillance Application, IR remote control and mouse operation, 4-ch video&1-ch audio input, 1 SATA interface, WD1/4CIF/2CIF: 12 fps/ch, 1U case.CIF real-time recording, 1 SATA interface, HDMI output, Video loop out optional, Front panel buttons optional, Alarm I/O: 4/1 and 4 audio input optional.
TRC 012 16CH		16 Channel DVR Solution: H.264, Dual-Stream, Multi-channel synchro playback, HDMI, VGA, CVBS output, 2*USB 2.0, RS485, Include CVMS (Central Video Management Software) and Mobile Surveillance Application, IR remote control and mouse operation, 4-ch video&1-ch audio input, 1 SATA interface, WD1/4CIF/2CIF: 12 fps/ch, 1U case.CIF real-time recording, 1 SATA interface, HDMI output, Video loop out optional, Front panel buttons optional, Alarm I/O: 4/1 and 4 audio input optional.	WRC 099A 4 CH		4 Channel DVR Solution Real Time: H.264,4CIF real-time recording, Dual-Stream, Multi-channel synchro playback, HDMI, VGA, CVBS output, 2*USB 2.0, RS485, Include CVMS (Central Video Management Software) and Mobile Surveillance ApplicationIR remote control and mouse operation,4CIF real-time recording, 1 SATA interface(4-ch), 2 SATA interfaces(8/16- ch), HDMI output, Video loop out optional, Front panel buttons optional, Alarm I/O: 4/1, 8/4, 16/4 and 4/8/16 audio input optional respectively, 4-ch video&1-ch audio input, 1 SATA interface, 4CIF: 25(P) / 30(N) fps/ch, 1U case.
WRC 100A 8 CH		8 Channel DVR Solution Real Time: H.264, 4CIF real-time recording, Dual-Stream, Multi-channel synchro playback, HDMI, VGA, CVBS output, 2*USB 2.0, RS485, Include CVMS (Central Video Management Software) and Mobile Surveillance ApplicationIR remote control and mouse operation,4CIF real-time recording, 1 SATA interface(4-ch), 2 SATA interfaces(8/16-ch), HDMI output, Video loop out optional,Front panel buttons optional, Alarm I/O: 4/1, 8/4, 16/4 and 4/8/16 audio input optional respectively, 8-ch video&1-ch audio input, 2 SATA interfaces,4CIF: 25(P) / 30(N) fps/ch, 1U case, 19"	WRC 101A 16 CH		16 Channel DVR Solution Real Time : H.264, 4CIF real-time recording, Dual-Stream, Multi-channel synchro playback, HDMI, VGA, CVBS output, 2*USB 2.0, RS485, Include CVMS (Central Video Management Software) and Mobile Surveillance ApplicationIR remote control and mouse operation,4CIF real-time recording, 1 SATA interface(4-ch), 2 SATA interfaces(8/16-ch), HDMI output, Video loop out optional,Front panel buttons optional, Alarm I/O: 4/1, 8/4, 16/4 and 4/8/16 audio input optional respectively, 16-ch video&1-ch audio input, 2 SATA interfaces,4CIF: 25(P) / 30(N) fps/ch, 1U case, 19"
WRC 186 4CH		4 Channel DVR Solution: H.264, Dual-Stream, Multi-channel synchro playback, HDMI, VGA, CVBS output, 2*USB 2.0, RS485, Include CVMS (Central Video Management Software) and Mobile Surveillance Application, IR remote control and mouse operation, 4-ch video&1-ch audio input, 1 SATA interface, WD1/4CIF/2CIF: 12 fps/ch, 1U case.CIF real-time recording, 1 SATA interface, HDMI output, Video loop out optional, Front panel buttons optional, Alarm I/O: 4/1 and 4 audio input optional.	WRC 187 8 CH		8 Channel DVR Solution: H.264, Dual-Stream, Multi-channel synchro playback, HDMI, VGA, CVBS output, 2*USB 2.0, RS485, Include CVMS (Central Video Management Software) and Mobile Surveillance Application, IR remote control and mouse operation, 4-ch video&1-ch audio input, 1 SATA interface, WD1/4CIF/2CIF: 12 fps/ch, 1U case.CIF real-time recording, 1 SATA interface, HDMI output, Video loop out optional, Front panel buttons optional, Alarm I/O: 4/1 and 4 audio input optional.
WRC 188 16 CH		16 Channel DVR Solution: H.264, Dual-Stream, Multi-channel synchro playback, HDMI, VGA, CVBS output, 2*USB 2.0, RS485, Include CVMS (Central Video Management Software) and Mobile Surveillance Application, IR remote control and mouse operation, 4-ch video&1-ch audio input, 1 SATA interface, WD1/4CIF/2CIF: 12 fps/ch, 1U case.CIF real-time recording, 1 SATA interface, HDMI output, Video loop out optional, Front panel buttons optional, Alarm I/O: 4/1 and 4 audio input optional.	WRC 154 4 CH		*4 Channel camera images,FULL 960H. *Playback simultaneously by 4 cameras in real time 1080p. *Supports hard disk 1 child up to 4TB.

WRC 155 8 CH		*8 Channel camera images FULL 960H *Playback simultaneously by 4 cameras in real time 1080p. *Supports hard disk 1 child up to 4TB.	WRC 156 16 CH		*16 Channel camera images FULL 960H *Playback simultaneously by 4 cameras in real time 1080p. *Supports hard disk 1 child up to 4TB.
WRC 124H 4 CH		*4 Channel camera images FULL D1. *Playback simultaneously by 4 cameras in real time 1080p. *Supports hard disk 1 child up to 4TB.	WRC 125H 8 CH		*8 Channel camera images FULL D1 *Playback simultaneously by 4 cameras in real time 1080p. *Supports hard disk 1 child up to 4TB.
WRC 126H 16 CH		*16 Channel camera images FULL D1 *Playback simultaneously by 4 cameras in real time 1080p. *Supports hard disk 1 child up to 4TB.	WRC 131A 8 CH		*8 Channel camera images. *Playback simultaneously by 4 cameras in real time 1080p. *Support 2 SATA HDD up to 8TB, 2 USB2.0
WRC 132A 16 CH		*16 Channel camera images. *Playback simultaneously by 16 cameras in real time 1080p. *Support 2 SATA HDD up to 8TB, 2 USB2.0	WRC 118 16 CH		*16 channels per pixel cameras and audio. *Recording FULL D1. *Select Display multiple HDMI, VGA, AV, TV USB2.0 *Insert the disk Hart had 4 children, up to 2TB.
WRC 168 24 CH		*24 channels per pixel cameras and audio. *Recording FULL D1. *Select Display multiple HDMI, VGA, AV, TV USB2.0. *Insert the disk Hart had 2 children, up to 4TB.	WRC 169 32 CH		*32 channels per pixel cameras and audio. *Recording FULL D1. *Select Display multiple HDMI, VGA, AV, TV USB2.0. *Insert the disk Hart had 2 children, up to 4TB.
WRC 3232L 32CH		32 channels per pixel cameras and audio. *Recording FULL CIF. *Select Display multiple HDMI, VGA, AV, TV USB2.0. *Insert the disk Hart had 2 children, up to 4TB.	WRC 102A 32 CH		*32 Channel camera images. *Playback simultaneously by 32 cameras in real time 1080p. *Supports hard disk 4 child up to 4TB.
WRC 091H 32 CH		*32 channels per pixel cameras and audio. *Recording FULL D1. *Select Display multiple HDMI, VGA, AV, TV USB2.0. *Insert the disk Hart had 8 children, up to 4TB.			

NETWORK DVR

WRC 143 NVR 8 CH		Up to 8/16/32 channel with 1080p realtime live view H.264/MJPEG dual codec decoding Up to 5Mp resolution Max 240fps@1080p, 480fps@720p, 960ps@D1 preview & recording HDMI / VGA simultaneous video output 16 channel synchronous realtime playback, GRID interface Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotech and etc. ONVIF Version 2.0 conformance 3D intelligent positioning with Dahua PTZ camera Support 2 SATA HDDs up to 8TB, 2 USB2.0 Multiple network monitoring: Web CMS(DSS/PSS) & DMSS	WRC 144 NVR 16 CH		Up to 8/16/32 channel with 1080p realtime live view H.264/MJPEG dual codec decoding Up to 5Mp resolution Max 240fps@1080p, 480fps@720p, 960ps@D1 preview & recording HDMI / VGA simultaneous video output 16 channel synchronous realtime playback, GRID interface Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotech and etc. ONVIF Version 2.0 conformance 3D intelligent positioning with Dahua PTZ camera Support 2 SATA HDDs up to 8TB, 2 USB2.0 Multiple network monitoring: Web CMS(DSS/PSS) & DMSS
-----------------------------	---	---	------------------------------	---	---

Dome Camera

WCI 213		STD-31-70D3BR 1/3" DIS, 700TVL, with ICR LED 2PCS IR Distance: 20M LENS: 3.6MM	WCI 192		CMOS 800TVL IR LED 1PCS IR Distance 10-30M Lens 3.6mm/6mm
WCIG 227		CMOS 800TVL IR LED 6PCS IR Distance 20M Len 3.6mm	WCIG 232		CMOS 800TVL IR LED 24PCS IR Distance 20M Len 3.6mm/6mm

WCIG 226		PANASONIC 700TVL IR LED 6PCS IR Distance 20M Lens 3.6mm			
Infrared Camera					
WCI 145AM		SONY 650TVL IR LED 36PCS IR Distance 50M Lens 6mm	WCI 173		SONY CCD 700TVL IR LED 1PCS IR Distance 30M Lens 4mm/6mm
WCI 174		SONY 700TVL IR LED 1PCS IR Distance 30M Lens 4mm/6mm	WCI 193		SONY 700TVL、OSD、Array of light sources F1.2HD Lens 4mm/6mm/8mm Face Recognition
WCI 076AM		SONY 700TVL IR LED 48pcs IR Distance 40M(HLC) Lens 4-9mm (UTC OSD,HLC)	WCI 137		SONY 700TVL IR LED 2PCS IR Distance 80M Lens 4-9mm(HLC)
WCI 139		SONY 750TVL IR LED 8PCS IR Distance 30M Lens 4-9mm(HLC)	WCIG 220		Panasonic 700TVL IR LED 2PCS IR Distance 30-50M Lens 3.6mm/6mm/8mm
Infrared Cmos Camera					
WCI 191		DIS 700TVL IR LED 1PCS IR Distance 40M Lens 3.6mm/6mm	WCI 063CA		CMOS 1/3" HDIS 800TVL 24pcs IR LEDS IR Distance 15-20m LENS:3.6mm DWS, no DFIR and fog Hidden cable bracket
WCI 228		CMOS 800TVL IR LED 36pcs IR Distance 30M Lens 3.6mm/6mm	WCIG 259		CMOS 1/3" HDIS 800TVL IR-CUT 1pcs Array IR LED IR Distance 15-20m 3.6mm, 6mm, 8mm optional DWS, no DFIR and fog Metal housing IP66
WCI 202		CMOS 800TVL IR LED 2pcs IR Distance 80M Lens 3.6mm/6mm	WCI 195		CMOS 850TVL IR LED 2pcs IR Distance 50M Lens 6mm/8mm
WCI 157A9		COMS CCD CAMERA IR NO.IV-1Y91PC 1/3 COMS 900 TVL IR Distance:40M LENS:3.6MM/6 MM.	WCIG 257		COMS 1/2" TK-618 1200TVL With 1pcs array LED NO.HD1-755 IR Distance:80M LENS: 3.6MM/6MM/8MM
Fix Camera					
WCB 057		SONY 650TVL WDR (UTC OSD,HLC)	WCZ 008		SONY 700TVL 27X optical zoom Auto focus with high-speed, focus clearly only once (OSD,HLC)
WCB 062		SONY 720TVL (UTC OSD,HLC,DWDR)			

Spy Camera					
WCM 003		SONY 420TVL Lens 3.6mm	WCM 030		SONY 700TVL Lens 2.8mm/3.7mm/6mm one audio
Speed Dome Camera					
WSPG 048 6inch		●SONY CCD 650TVL ●Make use of 30x HD color zoom camera as module. ●Rotate 360°in horizontal direction, Vertical 90°continuous monitoring after auto reversing 180° ●Focus length 3.9~39.0mm ●high speed ●Built-in OSD ●Outdoor used	WSPG 049 6inch		●LG CCD 700TVL ●Make use of 23x HD color zoom camera as module. ●Horizontal range 360°unlimited rotation,Vertical range - 10~90° ●Focus length 3.2~86.4mm ●high speed ●Built-in OSD ●Autofocus White Balance Backlight Compensation ●Outdoor used
WSPG 043 4inch MINI		●SONY CCD 650TVL ●Make use of 10x HD color zoom camera as module. ●Rotate 360°in horizontal direction, Vertical 90°continuous monitoring after auto reversing 180° ●Focus length 3.9~39.0mm ●IR distance 35M ●high speed ●Built-in OSD ●Indoor used	WSPG 044 4inch MINI		●SONY CCD 650TVL ●Make use of 10x HD color zoom camera as module. ●Rotate 360°in horizontal direction, Vertical 90°continuous monitoring after auto reversing 180° ●Focus length 3.9~39.0mm ●IR distance 35M ●high speed ●Built-in OSD ●Indoor used
WSPG 045 4inch MINI		●SONY CCD 700TVL ●Make use of c 10x HD color zoom camera as module. ●Rotate 360°in horizontal direction, Vertical 90°continuous monitoring after auto reversing 180° ●Focus length 3.9~39.0mm ●IR distance 60M ●Built-in OSD ●Indoor used	WSPG 046 4inch MINI		●SONY CCD 700TVL ●Make use of Automatic 10x HD color zoom camera as module. ●Rotate 360°in horizontal direction, Vertical 90°continuous monitoring after auto reversing 180° ●Focus length 3.9~39.0mm ●IR distance 60M ●Built-in OSD ●Indoor used
RS719-H/G 7inch		●SONY CCD 650TVL, 7inch ●Make use of 30x HD color zoom camera as module. ●Rotate 360°in horizontal direction, Vertical 90°continuous monitoring after auto reversing 180° ●Focus length 3.9~39.0mm ●IR distance 150M ●high speed ●Built-in OSD ●Outdoor used	M6RX- E/L/H/S 6inch		●SONY CCD 700TVL ●Make use of 27x HD color zoom camera as module. ●Horizontal range 360°unlimited rotation,Vertical range - 10~90° ●Focus length 3.2~86.4mm ●IR distance 80~120m ●constant speed ●Built-in OSD ●Outdoor used

H6RX-E/L/H/S 6inch		●SONY CCD 700TVL ●Make use of 27x HD color zoom camera as module. ●Horizontal range 360°unlimted rotation,Vertical range - 10~90° ●Focus length 3.2~86.4mm ●IR distance 80~120m ●high speed ●Built-in OSD ●Outdoor used			
Control Keyboard					
SWR-2D		ball machine, two-dimensional control of the keyboard decoder	AT803-3D		ball machine, three-dimensional control of the keyboard decoder (D English key display)
SWR-3D		ball machine, three-dimensional control of the keyboard decoder	K1604M		speed dome control keyboard (three-dimensional), can control 128 Speed Dome
Bracket					
WBK 302		Steel Bracket for Camera	WAC 013		Steel Bracket for Camera Dimension : 245mm
WLA 018		Plastic Bracket for Camera Length 160mm	WBK 890B		Bracket White
WBK 209		Monitor bracket IR viewon alloy stent lensgth 12cm	WBK 558		Steel Bracket for Camera Dimension : 145mm
WBK 007		Steel Bracket for Camera Length 205mm			
Camera Cable					
WC 001		Cable RG6 / 128 100M Description : RG 6/U Cable 75 ohms Copper clad steel : 95% Standard : Indoor	WC 002		Cable RG6 / 128 200M Description : RG 6/U Cable 75 ohms Copper clad steel: 95% Standard : Indoor

WC 305		Cable RG6 / 128 305M Description : RG 6/U Cable 75 ohms Copper clad steel: 95% Standard : Indoor	WCP 004 500M		Cable RG6 / 160 500M Description : RG 6/U Cable 75 ohms Copper clad steel : 95% Standard : Indoor
WCP 061 100M		*Cable and RG59 / U power cable with the same line. *Cable Knit 160 shield (95%) shielding. *Size of 0.75mm wire. *Length 100 meters. *The ability to send a signal to 1-500m.	WCP 062 200M		*Cable and RG59 / U power cable with the same line. *Cable Knit 160 shield (95%) shielding. *Size of 0.75mm wire. *Length 200 meters. *The ability to send a signal to 1-500m.
WCP 063 300M		*Cable and RG59 / U power cable with the same line. *Cable Knit 160 shield (95%) shielding. *Size of 0.75mm wire. *Length 300 meters. *The ability to send a signal to 1-500m.	WCP 064 500M		*Cable and RG59/ U power cable with the same line. *Cable Knit 160 shield (95%) shielding. *Size of 0.75mm wire. *Length 500 meters. *The ability to send a signal to 1-500m.
WCP 039T 100M		*Cable and RG6 / U power cable with the same line. *Cable Knit 160 shield (95%) shielding. *Size of 0.75mm wire. *Length 100 meters. *The ability to send a signal to 1-500m.	WCP 042T 200M		*Cable and RG6 / U power cable with the same line. *Cable Knit 160 shield (95%) shielding. *Size of 0.75mm wire. *Length 200 meters. *The ability to send a signal to 1-500m.
WCP 043T 300M		*Cable and RG6 / U power cable with the same line. *Cable Knit 160 shield (95%) shielding. *Size of 0.75mm wire. *Length 300 meters. *The ability to send a signal to 1-500m.	WCP 044T 500M		*Cable and RG6/ U power cable with the same line. *Cable Knit 160 shield (95%) shielding. *Size of 0.75mm wire. *Length 500 meters. *The ability to send a signal to 1-500m.
BNC+DC 5M		Video BNC Cable + Power DC Cable	BNC+DC 10M		Video BNC Cable + Power DC Cable
BNC+DC 15M		Video BNC Cable + Power DC Cable	BNC+DC 20M		Video BNC Cable + Power DC Cable
BNC+DC 30M		Video BNC Cable + Power DC Cable	BNC+DC 40M		Video BNC Cable + Power DC Cable

BNC+DC 50M		Video BNC Cable + Power DC Cable			
Booster & PTZ					
WTP 001 306		Pan Scanner Indoor Pan Angular 355/sec Pan Speed 6 /Sec,220V	WTP 002		Pan/Tilt Scanner Indoor Pan Angular 350 / sec, Tilt Anglar 60 / sec, Pan Speed 6 / Sec,
WTP 010		Pan/Tilt Scanner Indoor Pan Angular 350/ sec, Tilt Anglar 60 / sec, Pan Speed 6 / Sec,	WTP 005		Control Up, Down, Left Right and Auto Pan Control for WTP010
WBT 002 AV-104		*4 channel Audio Video Distributor *Video Input1/Video Output 4 *Audio Input1/Audio Output 4	WBT 003 AV-108		*12 channel Audio Video Distributor *Video Input1/Video Output 12 *Audio Input1/Audio Output 12
Magnetic&Bolt Lock					
WHS 001		Outdoor/Indoor Camera Housing Dimension: 178X158X400mm	WHS 002		Outdoor/Indoor Camera Housing Dimension: 120X108X410mm
WHS 003		Outdoor/Indoor Camera Housing Dimension: 142X115X390mm	WHS 004		Outdoor/Indoor Camera Housing Dimension: 120X108X410mm
WHS 015		Indoor Camera Housing Dimension: 98X80X281mm	WHS 016		Indoor Camera Housing Dimension: 98X80X281mm
Magnetic&Bolt Lock					
WKC 010		Electromagnetic Lock For 1 way swing door, Wooden door , Glass door, Fail Safe Type, DC 12V	WKC 012		Electric plug lock Bolt Lock For 2 way Swing door, Wooden door, Glass Door Fail Safe Type
WKC 013		Bracket for frameless glass door	WKC 014		Entrance guard bracket of ZL Bracket for inward door

WKC 015		Entrance guard u-shaped bracket Bracket for frameless glass door	WKC 016 ABK-700 Stents		Bracket for fully frameless glass door
Doorphone/Alarm					
Wireless video door bell		Doorbell 7 "inch LED, 1/3 SONY CCD camera	Smoke detector		WIR viewed smoke detector WIR view to 4-pin 12V alarm WIR viewed networking
Normally open normally closed switch		Entrance guard switch device			
Singer Door					
WKI 001		ID Card	WKI 002		ID Card
WKC 046		Pin Proximity Singer door Operation Mode: Card, Card+Code, UID+Code, Supercode	WKC 047		Pin Proximity Singer door Operation Mode: Card, Card+Code, UID+Code, Supercode
Finger Scan					
WSF 003		FINGER SCAN Model WF7	WSF 004		FINGER SCAN Model AF4
WSF 010		FINGER SCAN Model WZ2			
Accessory					

WUTP 202L		1 Channel Video Balun 1 Video / Power in 1 Video / Power out UPT up to 300 Meter	WUTP 006		Video : DC - 6 MHz Common-mode/Differential-mode: 15khz - 6Mhz 60dB Impedance : Coax 750Ohm/Twisted Pair 100Ohm Dimensions(mm) : 1.84 (L)*.54(W)*0.6(H) Weigh(g) :18g
WUTP 012		UTP Converter 4 Channel Passive Video Balun 4 Video / Power in 4 Video / Power out UPT up to 300 Meter	WAC 001A		MINI MICROPHON
SP-15E		MICROPHONE			

Power Supply

WKC 018		Input AC 200-230V 50 HZ Output DC 12V/3A With NC/NO and Timer	WKC 048		The power supply DC 12V Switching. Maximum current 5Amp. Input : 100-240VAC Out put :12VDC,+/- 5% Support Camera : 8 pcs.
WKC 029		Power Access Control Input : AC 200-230V ,50Hz Output:DC 12V / 3A			

Camera Adapter

WKC 064		OUTPUT:12V-5A	WKC 073		OUTPUT:12V-10A
WKC 074		OUTPUT:12V-15A	WKC 071		OUTPUT:12V-20A
WKC 072		OUTPUT:12V-30A	waterproof power supply DC		OUTPUT:12V-10A
waterproof power supply DC		OUTPUT:12V-15A	waterproof power supply DC		OUTPUT:12V-20A

waterproof power supply DC		OUTPUT:12V-30A	power supply DC		OUTPUT:12V-20A 9CH
power supply DC		OUTPUT:12V-30A 18CH	WAC 180		12V 1500mA
WAC 209		12V 1500mA	WAC 210		12V 1500mA
WAC12V3A		12V 3A	DW-2007015		Outdoor Waterproof Power 12V 1500mA
DW-200802		Outdoor Waterproof Power 12V 2000mA			

Lens Camera

WLA 006		LENS AUTO Iris 3.5-8mm	WLA 007		LENS AUTO Iris 2.8-12mm
WLA 008		LENS AUTO Iris 6-15mm	WLA 010		LENS AUTO Iris 6-60mm

Alarm

MC06-1		Doors and Windows alarm	JS-312		Infrared sensor alarm human body
---------------	---	-------------------------	---------------	---	----------------------------------

Camera BNC

75-3 flat A three-piece			75-4 flat A three-piece		
75-5 flat A three-piece			BNC spring The plug flat		
BNC spring The plug good			BNC F for F		
BNC TO AV M			BNC M The pass-through		
BNC TO F good			AV		
DC M			AV good		
BNC M TO AV F			DC F		
BNC clip mouth			BNC hexagon		
BNC F spring			AV M The pass-through		
Antenna Connector			American BNC		
BNC F Tee			T type		

BNC TO F flat			BNC F Pressure welding		
T Tee			BNC M TO AV M		
BNC Pressure welding flat			F Tee		
DC TO BNC M			Threaded head		